

PRODUCT DATA SHEET

Cromar[®] Continuous Rafter Tray

Roll out rafter trays are an effective way of preventing loft insulation from moving

PRODUCT DESCRIPTION

Roll out rafter trays are an effective way of preventing loft insulation from moving up to the underside of a roof underlay.

They provide a uninterrupted means of air access into the roof from the eaves. Suitable for 400, 450 and 600 rafter centres.

USES

- Roof ventilation and condensation management.

PRODUCT INFORMATION

Packaging	Boxed
Colour	Black
Shelf Life	As a plastic item there is no specific shelf life
Storage Conditions	The product should be stored properly in original, unopened and undamaged sealed packaging, in dry conditions at temperatures between +5 °C and +30 °C.
Length	6 metre
Width	600 mm

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

CHARACTERISTICS / ADVANTAGES

- Allows a constant flow of air between the loft space and outside meaning built up moisture can escape.
- Lightweight and durable solution.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH: This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the

product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

Roll the trays over the rafters in right position to provide a clear air access above the roof insulation, and fix the trays to the rafters by using staples or clout head nails. If it is a low pitch pitched roof, you may have to join two trays together. When using soffit ventilation the bottom of the tray must be kept at a minimum of 25 mm from the back of the fascia board.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Cromar® Continuous Rafter Tray
April 2026, Version 01.01
020945201000247263

CromarContinuousRafterTray-en-IE-(04-2026)-1-1.pdf

