

PRODUCT DATA SHEET

Sikatherm[®] PIR BN RK1

BITUMEN COATED GLASS TISSUE FACED PIR THERMAL INSULATION BOARD

PRODUCT DESCRIPTION

Sikatherm[®] PIR BN RK1 is an insulation board for flat Roofing. It is faced on both sides with a coated glass tissue bonded to the insulation core with the top surface being coated in bitumen and produces a tough, durable, light weight insulation board.

USES

Thermal insulation for use underneath specified Sika[®] roof waterproofing system

CHARACTERISTICS / ADVANTAGES

- High performance rigid insulation
- Compatible with majority of torch applied water-proofing systems
- Resistant to passage of water vapour
- Easy to handle and install
- Manufactured with blowing agent that has zero ODP and low GWP

PRODUCT INFORMATION

Packaging	Full length and width boards in protective wrapping		
Shelf Life	5 years from date of production		
Storage Conditions	The polyethylene polythene packaging, which is recyclable, should not be considered adequate for outdoor protection. Ideally, boards should be stored inside a building. If, however, outside storage cannot be avoided, then the boards should be stacked clear of the ground and covered with an opaque polythene sheet or weatherproof tarpaulin. Boards that have been allowed to get wet should not be used.		
Dimensions	1200 x 600mm Boards		
Compressive Strength	150 kPa (at 10% compression)		
Thermal Conductivity	Thickness	Thermal Conductivity	(EN 12667 / EN 12939)
	<80mm	0.026 W/mK	
	80 - 119mm	0.025 W/mK	
	>120mm	0.024 W/mK	

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER DOCUMENTS

Installation work must only be carried out by Sika[®] trained contractors, experienced in this type of application.

- The product is not classified as hazardous good for transport. Local safety regulations must be observed.
- During the construction process, the construction should be protected from rain penetration during breaks in the process.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

REGULATION (EC) NO 1907/2006 - REACH: This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

SUBSTRATE QUALITY

The substrate surface must be uniform, smooth and free of any sharp protrusions or burrs, etc. It must be clean, dry and free of grease and dust.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @Sikalreland



Product Data Sheet
Sikatherm® PIR BN RK1
November 2021, Version 01.01
020935011000000017

SikathermPIRBNRK1-en-IE-(11-2021)-1-1.pdf

