

PRODUCT DATA SHEET

Sika® Path & Patio Sealer

For sealing and protecting patios, paving and stonework

PRODUCT DESCRIPTION

Sika® Path & Patio Sealer is a water-based solution that seals and protects outdoor surfaces against the effects of water, dirt, petrol, grime, and green growth. It enhances durability and helps keep patios looking clean for longer.

USES

- Paths.
- Patios.
- Block paving.
- Indian sandstone.
- Natural stone, such as limestone.

CHARACTERISTICS / ADVANTAGES

- New, refurbished or recently cleaned surfaces.
- Protects against weather, staining and green growth.
- Dries clear.

PRODUCT INFORMATION

Chemical Base	Water-based Acrylic and Polyurethane Dispersion
Packaging	5 L
Colour	White liquid
Shelf Life	12 months from date of manufacture unopened
Storage Conditions	Store upright, sealed, in a cool, dry, ventilated place at +5 °C to +25 °C. Protect from frost and direct sunlight.
Consumption	1 L per 5-6 m ² per coat

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Use only as directed. Store only in original container.
- Do not use on surfaces which have been treated with silicone or stearate based water seals (eg Sika®

Waterproofer & Protector) unless the surface is weathered enough so as to show no water beading effects.

- Do not use if rain is imminent (within 5 hours at +20 °C).
- Do not apply below +5 °C (air or surface temp).
- Dispose of this product and packaging correctly. Do not allow to enter watercourses. It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for further advice.

ECOLOGY, HEALTH AND SAFETY

Local safety regulations must be observed and it advisable to wear PPI when working with this product with particular attention paid to cutting and handling. Transportation Class: The product is not classified as hazardous good for transport. Disposal: The material is recyclable. Disposal must be according to local regulations. Please contact your local Sika sales organisation for more information.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

- Ensure surface is clean, dry or damp (not wet), and free from grease, loose material, and green growth.
- Do not apply to paving laid less than 3 months ago.
- Avoid surfaces treated with silicone or stearate-based sealers.
- Always test on a small area before full application.

APPLICATION

- Stir thoroughly before use.
- Do not apply if rain is expected within 5 hours.
- Apply using a long-pile roller, brush, or low-pressure garden spray.
- Do NOT pour directly onto the surface – apply evenly.
- Apply in dry weather above +5 °C.
- Once applied, surface will be dry to touch in approx. 30 minutes; walk-on in 1 hour.
- Allow 1 hour between coats if applying more than one coat.

Recommended Coats:

Very porous substrates: e.g. concrete flags, some stones:-

2 coats, wait 2 hours between coats.

Low porosity substrates: e.g dense block paving:-
1 coat is usually sufficient.

CLEANING OF TOOLS

Clean equipment with water and detergent immediately after use.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland



Product Data Sheet

Sika® Path & Patio Sealer
November 2025, Version 01.01
021890100000245330

SikaPathPatioSealer-en-IE-(11-2025)-1-1.pdf

